

# PH 26

## 26 mm SDS-plus 3-mode hammer

### Features

- Most compact, slimline hammer available in its class
- Unmatched performance with 2.4 J blow energy and 4500 bpm
- Lowest vibration only 13.5 m/s<sup>2</sup>
- Extreme Milwaukee® durability thanks to integrated metal block technology
- Innovative and patented internal weight reduction technology
- Hammer stop function
- Safety clutch protects machine and user if drill bit jams
- X version comes with fast changing FIXTEC adaptor with keyless chuck
- 4 m cable



<b>RANGE SPEC (1)</b>	<b>PH 26</b>	<b>PH 26 X</b>
Sound pressure level (dB(A))	92	92
Sound pressure level uncertainty (dB(A))	3	3
Sound power level (dB(A))	103	103
Sound power level uncertainty (dB(A))	3	3
Vibration chiselling uncertainty (m/s <sup>2</sup> )	1.5	1.5
Vibration drilling into concrete [m/s <sup>2</sup> ]	13.5	13.5
Vibration drilling into concrete uncertainty [m/s <sup>2</sup> ]	1.5	1.5
Supplied in	Kitbox	Kitbox
Vibration drilling (m/s<special id="27"/>)	13.5	13.5
Vibration chiseling (m/s<special id="27" />)	11.2	11.2
Article Number	4933387400	4933387470
Weight (kg)	2.4	2.6
Power input (W)	725	725
Max. drilling steel (mm)	13	13
Max. drilling wood (mm)	30	30
Max. drilling concrete (mm)	26	26
Full load hammer action (bpm)	0 - 4500	0 - 4500
Full load speed (rpm)	0 - 1250	0 - 1250
Blow energy (EPTA)(J)	2.4	2.4